


[Web](#) [Images](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more](#) ▼

[Sign in](#)



add behavior to a subclass through attribute at runtime

Search

[Advanced Search](#)
[Preferences](#)



Web Results 1 - 10 of about 190,000 for add behavior to a subclass through attribute at runtime. (0.32 seconds)

Did you mean: add behavior to a subclass through attribute at **runtime**

[PDF] The Dynamic Template Pattern

File Format: PDF/Adobe Acrobat - [View as HTML](#)

impossible) to **add behavior** to a class at **runtime**, what we create are not "real" ... **attributes through** a method to specify whether the **attributes** are to be ...

st-www.cs.uiuc.edu/~hanmer/PLoP-97/Proceedings/lyardet.pdf - [Similar pages](#)

The Essence of OOP using Java, **Runtime** Polymorphism **through** ...

The benefits of **runtime** polymorphic **behavior** generally accrue when the actual type of the object is a **subclass** of the type of the reference variable ...

www.developer.com/java/other/article.php/983081 - 121k - [Cached](#) - [Similar pages](#)

Refining the Type Object Pattern: the Class Object Pattern

Thus repeating all that information **through** all copies of "Star Wars" is redundant. You want to be able to **add** class or instance **attributes** in **runtime**. ...

www-lilia.info.unip.edu.ar/~fer/classof.html - 26k - [Cached](#) - [Similar pages](#)

Cocoa Fundamentals Guide: Basic **Subclass** Design

When you **add** instance variables to a **subclass**, it's worthwhile to heed a few ... at the beginning of their **runtime** life and just before their destruction. ...

developer.apple.com/.../Conceptual/CocoaFundamentals/AddingBehaviortoCocoaProgram/chapter_4_section_5.html - 98k - [Cached](#) - [Similar pages](#)

DataObject Tutorial

SimpleDataObject is a **Subclass** of AbstractDataObject; if you want a DataObject class which allows you to **add** extra **attributes at runtime**, you may want to ...

https://www.openadaptor.org/docs/DOTutorial.html - 32k - [Cached](#) - [Similar pages](#)

NHibernate 1.2 Migration Guide

Association fetching strategies; Schema namespace; One-to-many association to a **subclass** requires explicit where **attribute**. **Runtime** Changes ...

www.hibernate.org/407.html?cmd=prntdoc - 16k - [Cached](#) - [Similar pages](#)

Using a Custom **Subclass** of a JClient Control Binding

For the **runtime** code block, **add** a call to the constructor for your **subclass** ... JClient checks to see if the **attribute** is updateable or not (**through** a call ...

www.oracle.com/technology/products/jdev/howtos/JClient/JClient_Binding_Subclass.html - 71k - [Cached](#) - [Similar pages](#)

An Evolutionary Approach for Dynamic Reconfiguration in ...

the **behavior** between the **subclasses** is very similar or can be ... Property, **Attribute** and Association. An Association would. know its cardinality. ...

ieeexplore.ieee.org/iel5/11108/35623/01688364.pdf?tp=&isnumber=&arnumber=1688364 - [Similar pages](#)

System and method for defining and using **subclasses** declaratively ...

The name **attribute** 612 specifies a name for the property. In one embodiment, names are case sensitive and the **runtime** engine places no restrictions on the ...


www.patentsform.us/patents/7120618-description.html - 61k - [Cached](#) - [Similar pages](#)

Agile Ajax: Unit Tests

For my purposes, I let my IDE generate this **subclass** for me, While in other languages (such as Ruby) it is possible to **add behavior** to the concept of ...

blogs.pathf.com/agileajax/unit_tests/index.html - 62k - [Cached](#) - [Similar pages](#)

Did you mean to search for: [add behavior to a subclass through attribute at runtime](#)



add behavior to a subclass through attribute at runtime

Search

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#) | [Try Google Experimental](#)

©2008 Google - [Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)